

Flow Characteristics and Energy Dissipation Over Single Step Broad – Crested Weirs

Dr. Hamid H. Hussein
Shareef

Assist. Professor
Technical College/
Mosul

Inam A. K. Juma

Lecturer
Engineering College
University of Mosul

Saleh J. S.

Assist. Lecturer
Technical College/
Mosul

ABSTRACT

The main purpose of traditional broad - crested weir is to rise and control upstream (U/S) water level. In this study a new performance was added to this weir, by making it as an energy dissipater. In order to study the energy dissipation percent (E%), the downstream (D/S) height of the weir (12 cms U/S height) was reduced four times as 9.8,8,6and3.8cms. Thirty experiments were performed in a laboratory horizontal channel of 12 m length, 0.5 m width and 0.45 m depth for a wide range of discharge.

A mathematical model to compute theoretical coefficient of discharge (Cdth) was modified depending upon momentum equations. Experimental results gave a high validity to the computed values of the proposed model. On the other hand, three empirical non dimensional relations were obtained. The first is liner relation to estimate the ratio for D/S water head to U/S weir height (h/P1) in terms of the ratio for U/S water head to U/S weir height (H/P1). The second relation is nonlinear relation to estimate the discharge coefficient (Cd) in terms of H/P1 and the ratio of D/S weir height to U/S weir height (P2/P1). While the third relation is to estimate E% in terms of h/P1and P2/P1 with high correlation coefficients. The experimental results of the study showed that E% increased up to 46%. Furthermore, Cd was improved and gets higher values in comparison with traditional weirs.

Key words: Hydraulic structure; Broad crested weirs ; Energy dissipation.

خصائص الجريان وتبديد الطاقة فوق الهدارات مفردة الدرجة ذات القمة العريضة

صالح جعفر سليمان شريف
الكلية التقنية/الموصل

إنعام علي قاسم جمعه
كلية الهندسة/جامعة الموصل

الدكتور حامد حمود حسين
الكلية التقنية/الموصل

ملخص

إن الغرض الرئيسي من الهدار ذو القمة العريضة التقليدي هو رفع مستوى الماء والسيطرة عليه في مقدم الهدار . في هذه الدراسة تم إضافة أداء جديد لهذا الهدار من خلال تبديده لطاقة جريان الماء. ولدراسة نسبة تبديد طاقة الجريان (E%) تم تخفيض منسوب مؤخر سطح الهدار (والذي ارتفاعه في المقدم 12سم) أربعة مرات وبمنايب 9.8,8,6,3.8 سم. تم اختبار ثلاثين تجربة في قناة مختبرية افقية ذات طول 12م وعرض 0.5 م وعمق 0.45 م ولمدى واسع من التصارييف. تم اشتقاق علاقة رياضية لحساب معامل التصريف النظري (Cdth) بالاعتماد على معادلات زخم الطاقة ، وأعطت النتائج المختبرية تطابق جيد مع القيم المحسوبة بهذه المعادلة . من جانب آخر تم أستنباط ثلاث علاقات وضعية لابعدية. الأولى علاقة خطية لحساب (h/P1) بدلالة (H/P1) . أما العلاقة الثانية فكانت غير خطية لحساب Cd بدلالة نسبة عمق الماء مقدم الهدار الى ارتفاع الهدار في المقدم (H/P1) ونسبة ارتفاع مؤخر الهدار الى ارتفاع الهدار في المقدم (P2/P1). وكانت العلاقة الثالثة غير خطية أيضا لحساب E% بدلالة نسبة عمق الماء مؤخر الهدار الى ارتفاع الهدار في المقدم (h/P1) ونسبة ارتفاع مؤخر الهدار الى ارتفاع الهدار في المقدم (P2/P1) وبمعاملات ارتباط عالية . أظهرت النتائج المختبرية لهذه الدراسة بأن E% ازدادت بنسبة 46% . بالإضافة الى ذلك تحسن أداء هذا النوع من الهدارات حيث ازدادت قيم معامل التصريف Cd مقارنة مع الهدار ذو القمة العريضة التقليدي .

Notation:

The following symbols are used in this research:

B = channel width,

C_d = weir discharge coefficient,

$E\%$ = energy dissipation ratio,

$F\tau_o$ = boundary shear force,

see figure (1),

g = acceleration due to gravity,

H = U/S water head above the crest,

h = D/s water head,

L = length of the weir,

L_2 = length of D/S step,

P_1 = U/S weir height,

P_2 = D/S weir height,

q = discharge over the weir per unit width,

Q = Flow discharge,

R = radius of U/S corner of the weir,

Rn = Reynolds number

V_1 = velocity at sec.1,

V_2 = velocity at sec.2,

τ_o = boundary shear stress,

ν = kinematics viscosity of water.

μ = dynamic viscosity,

INTRODUCTION

Weirs with various shapes have been considered the most hydraulic structures which used in open channel flow. They are widely used in water flow measurements and control of water surface levels.

In order to prevent erosion and scouring in downstream (D/S) ends of weirs, the hydraulic energy should be dissipated. For this purpose, several ways were used such as lining by rubbles and riprap, or by constructing steps at D/S ends of weirs (Chanson, 2001).

In recent years, various investigators study the characteristics of flow over broad-crested weirs, Rao and Rao, (1973); Ackers, et al. (1978) verified an empirical relations for discharge coefficient (C_d), with inclined upstream face of this weir. Clemens, et al., (1984) provided a simplified design procedure covering a wide range of variables. Ramamurthy, et al., (1988) studied the characteristics of round-nosed broad-crested weir under free flow and submerged flow conditions. They derived a mathematical expression from momentum relations for (C_d). Furthermore, they found that when the ratio of the radius of U/S corner (R) to the height of the weir (P) $0.25 \leq R/P \leq 1$, the flow separation is essentially eliminated and (C_d) has attained the highest value. Chamani, (2002) presented a method for predicting both subcritical and supercritical flow characteristics over drops. He also derived an empirical relation to estimate the relative energy loss. Gonzalez and Chanson, (2007) estimated (C_d) over a large broad-crested weir, two empirical relations were presented depending on the geometry of the weir. Al-Talib (2007) investigated in a laboratory study the stepped and unstepped weirs for steep slope channels which is having high difference in head of water between upstream and downstream in order to find their efficiency for dissipating flow energy. She found that stepped weirs are more efficient than unstepped weirs and the maximum energy dissipation ratio in stepped weirs was approximately 10% higher than in unstepped weirs. Noori and Juma (2008) obtained two empirical equations to estimate the value of discharge coefficient in terms of effective head to crest height ratio, upstream corner radius to crest height ratio and radius of cap to crest height ratio

In this paper, D/S height of traditional broad-crested weir was reduced. This reduction gave the weir a new performance by making it as a water level controller and energy dissipater.

So, the main objectives of this paper are to study the flow characteristics, and dissipation energy D/S of the weir for mild slope channels or zero slope channels. Furthermore, to develop a mathematical relation of theoretical discharge coefficient depending on momentum equations. Also, to modify empirical relations for discharge coefficient and percentage of energy dissipation depending on affecting factors.

THEORETICAL ANALYSIS

1 –Experimental discharge coefficient, Cd

The functional relationship for Cd linking the main flow parameters (Figure 1) may be expressed as follows:

$$f_l (q , H , P_1 , L , R , P_2 , L_2 , g , \nu) = 0 \quad \text{----- (1)}$$

In which:

q = discharge over the weir per unit width,

H = U/S water head above the weir crest,

P₁ = U/S weir height,

L = length of the weir,

R = radius of U/S corner of the weir,

P₂ = D/S weir height,

L₂ = length of D/S step,

g = acceleration due to gravity,

ν = kinematics viscosity of water.

By dimensional analysis:-




Fig. (1) Free flow over Broad-crested weirs : (a) Traditional round-nosed weir; (b) Stepped weir.

$$Cd = \frac{q}{\frac{2}{3}H\sqrt{\frac{2}{3}gH}} = f_2\left(\frac{H}{P_1}, \frac{L}{P_1}, \frac{R}{P_1}, \frac{P_2}{P_1}, \frac{L_2}{P_1}, Rn\right) \quad \text{----- (2)}$$

Rn = Reynolds number which has very large values and hence its effect on Cd will be very little, therefore, Rn will be neglected in this study.

Since, L ; L_2 ; P_1 and R are fixed in this study then equation (2) can be rewritten as:-

$$Cd = f_3\left(\frac{H}{P_1}, \frac{P_2}{P_1}\right) \quad \text{----- (3)}$$

2 - Theoretical discharge coefficient, Cd_{th}

Ramamurthy, et al., (1988) introduced the following equation in their study to calculate Cd_{th} , but they neglect the effect of boundary shear over the surface of the weir.

$$F_1 + M_1 = F_p + F_3 + M_3 \quad \text{----- (4)}$$

Where:

$$F_1 = \frac{\gamma}{2}(H + P_1)^2 B$$

$$M_1 = \frac{\gamma}{g} \left(\frac{Q^2}{(H + P_1)B} \right)$$

$$F_p = kp \frac{\gamma}{2} [P_1(2H + P_1)B]$$

$$F_3 = \frac{\gamma}{2} h^2 B$$

$$M_3 = \frac{\gamma Q^2}{ghB}$$

The effect of boundary shear along the control surface over the weir was considered in this study and added to their equation.

$$F_1 + M_1 = F_p + F_3 + M_3 + F\tau_o \quad \text{----- (5)}$$

$$F\tau_o = \tau_o \times B \times L = \mu \frac{dv}{dy} BL \quad \text{----- (6)}$$

between sec. (1) and sec. (2) in Fig. (1)

$$F\tau_o = \frac{V_1 - V_2}{H - h} \times \mu \times B \times L \quad \text{----- (7)}$$

Substituting $Q = V_1 \times B \times H = V_2 \times B \times h$ in Eq. (7) gets:

$$F\tau_o = \frac{-Q\mu L}{H \times h} \text{----- (8)}$$

In which:

$F\tau_o$ = boundary shear force,

τ_o = boundary shear stress,

Q = Flow discharge,

V_1 = velocity at sec.1,

V_2 = velocity at sec.2,

B = channel width,

L = weir length,

μ = dynamic viscosity,

h = D/s water head.

The addition of equation (8) to equation (5) yields the following equation :

$$\frac{\gamma}{2}(H + P_1)^2 B + \frac{\gamma}{g} \left(\frac{Q^2}{(H + P_1)B} \right) = kp \frac{\gamma}{2} [P_1(2H + P_1)B] + \frac{\gamma}{2} h^2 B + \frac{\gamma Q^2}{ghB} - \frac{Q\mu L}{Hh} \text{-- (9)}$$

$kp=0.98$ as proposed by Ramamurthy, et al., (1988).

Discharge for broad -crested weir is:

$$Q = Cd \frac{2}{3} HB \sqrt{\frac{2}{3} gH} \text{----- (10)}$$

Substituting equation (10) in (9) with simplification yields:-

$$(H + P_1)^2 - h^2 - kp[2(2H + P_1)] = \frac{16}{27} H^3 Cd^2 \left[\frac{1}{h} - \frac{1}{H + P_1} \right] - \frac{4\mu L}{3\gamma h} \sqrt{\frac{2}{3} gH} Cd \text{-- (11)}$$

Let:

$$A_1 = \frac{16}{27} H^3 \left[\frac{1}{h} - \frac{1}{H + P_1} \right]$$

$$A_2 = \frac{4\mu L}{3\gamma h} \sqrt{\frac{2}{3} gH}$$

$$A_3 = (H + P_1)^2 - h^2 - kp[2(2H + P_1)]$$

Substituting A_1, A_2, A_3 in equation (11) gets:

$$A_1 Cd^2 - A_2 Cd - A_3 = 0 \text{----- (12)}$$

The roots of equation (12) are given by quadratic equation as:

$$Cd_{1,2} = \frac{A_2}{2A_1} \mp \left[\left(\frac{A_2}{2A_1} \right)^2 + \frac{A_3}{A_1} \right]^{1/2} \text{----- (13)}$$

Equation (13) will be used in this study to compute theoretical discharge coefficient (Cd_{th}).

3 – Energy Dissipation Ratio , E%

Based on energy relationships, the general relationship for the flow energy dissipation can be verified:

Applying energy equations between section (1) and section (2) in Fig. (1) we get:

$$E_1 = P_1 + H + \frac{V_1^2}{2g} \quad \text{----- (14)}$$

$$E_2 = P_2 + h + \frac{V_2^2}{2g} \quad \text{----- (15)}$$

$$E\% = \frac{E_1 - E_2}{E_1} * 100\% \quad \text{----- (16)}$$

On the other hand, the functional relationship for E% with the main flow parameters may be expressed as follows:

$$E\% = f_4(q, P_1, H, P_2, h, g, L) \quad \text{----- (17)}$$

By dimensional analysis:

$$E\% = f_5\left(\frac{H}{P_1}, \frac{P_2}{P_1}, \frac{h}{P_1}, \frac{L}{P_1}, \frac{q^2}{g.h^3}\right) \quad \text{----- (18)}$$

Since L and P_1 are fixed and h value related to H and $\frac{q^2}{gh^3}$ which is the Froude number at section (2), then equation (18) becomes:-

$$E\% = f_6\left(\frac{h}{P_1}, \frac{P_2}{P_1}, Fr_2\right) \quad \text{----- (19)}$$

EXPERIMENTAL SET- UP AND PROCEDURE

Tests were conducted in a horizontal, glass-walled rectangular channel of 10 m long, 0.50 m width and 0.45 m depth. Water surface levels were measured at different locations with an accurate point gauge reading to 0.1 mm. Discharge was measured by a pre-calibrated sharp-crested weir installed at the channel inlet (Plate 1). U/S flow heads were started to measure at a location (8H) U/S of the weir model .Five weir models were manufactured from thermostone and painted to decrease the surface roughness of these models. To ensure stability of water surface levels and uniform flow with very low turbulence, the models were fixed at a distance of 3.5m from the channel inlet.

One of the tested models was a traditional round – nosed broad – crested weir. It was 48cm long, 50 cm width and 12 cm height, the radius of the round nose was 6 cm. The other four models involved the above dimensions of the weir with D/S stepped length $L_2 = 24$ cm and D/S height $P_2 = 9.8, 8, 6$ and 3.8 cms.

All measurements were conducted at the center line of the channel width. In each test, U/S flow depth (H), water surface levels, D/S flow depth over the step (h), unit discharge (q) were measured.

The measurements along the weir models were conducted under the free

flow conditions. In all tests free-falling nappe at D/S step of models were fully aerated to prevent ventilation holes.



Plate (1) General view of the laboratory channel with one of the weir models

RESULTS AND DISCUSSION

1- Water surface Profiles

Dimensionless water surface profiles (w.s.ps.) over three weirs ($P2/P1 = 1, 0.5, 0.32$) were shown in Figures (2-4) which were measured in the center line of the channel. It can be seen that w.s.ps. were becomes horizontal when $X/P1 > 2$ where X is the U/S distance from the weir crest. These w.s.ps. were used to determine the average velocities and D/S water heads over the steps when w.s.ps. were essentially horizontal. The trend of these w.s.ps. were mostly similar, smooth and follow the shape of the weirs. Furthermore, in Figures (3) and (4) it can be seen clearly the effect of D/S steps on the w.s.ps.








Fig.(2) dimensionless water surface profiles for weir models of $p2/P1=1$




2- Weir Coefficients of Discharge

Figures (5) and (6) show the variation of experimental and theoretical C_d with $H/P1$ for the weir models ($P2/P1= 1, 0.5$), which were obtained using equations 10 and 13, respectively. In Fig. (5) for ($P2/P1=1$) the difference between experimental and theoretical C_d was about 4%. While in Fig. (6) for ($P2/P1= 0.5$) both values of C_d were nearly the same which gave a good agreement to the proposed model .






Also, in both figures, one may observe clearly that Cd increased significantly with the increase of H/P1. The variations of experimental Cd with H/P1 for the five models were shown in Fig. (7). Values of experimental Cd in all stepped models were obviously higher than experimental Cd in the traditional model (i.e., P2/P1=1). One may conclude that the presence of D/S steps can be contributed to accelerate the water flow and increase Cd.




3- Weir Energy Dissipation Ratio

One of the main objectives of this study is to determine the influence of D/S weir steps on the energy dissipation ratio E%. Fig. (8) Shows the effect of h/P1 and P2/P1 on E%. In this figure E% was decreased when h/P1 was increased for the last two weir models of P2/P1= 0.5 and 0.32 , while for the other models E% was approximately remains constant with the increase of h/P1 because the difference between P2 and p1 is small.



The variation of average values of Cd and E% with P2/P1 were shown in Fig. (9) from this figure it is observed clearly that both Cd and E% were decreased with the increase of P2/P1. Also, it is observed that the average values of Cd and E% at P2/P1 =0.5 and 0.32 were higher than the average values for other weirs respectively, generally Cd and E% are inversely proportional with P2/P1 because increasing P2 makes the weir model to be approximately same as traditional weir. From this figure It is obvious that the weir of P2/P1=0.4 gave Cd=0.968 and E%=37.




4. Empirical Relations

The relation between (h/P1) and (H/P1) for all models was shown in Figure (10). Furthermore, linear regression analysis was used to correlate h/P1 with H/P1 in an empirical linear relation;

$$h/P1 = 0.64(H/P1) - 0.08 \quad \text{----- (20)}$$

With a correlation coefficient = 0.992.



Based on equation (3), multiple nonlinear regression analysis was used to correlate C_d with both $(H/P1)$ and $(P2/P1)$ in an empirical power relation;

$$C_d = 0.96 \left(\frac{H}{P1} \right)^{0.058} \left(\frac{P2}{P1} \right)^{-0.03} \quad \text{----- (21)}$$

With a correlation coefficient = 0.83.

The relation between C_d values predicted by equation (21) and experimental values of C_d is plotted in Fig. (11) which shows a good agreement. Another empirical power relation based on equation (19) was obtained for the variation of $E\%$ with both $(h/P1)$ and $(P2/P1)$ (It was found that the effect of Fr_2 was very little on $E\%$ and it was neglected from the equation);

$$E\% = 6.56 \left(\frac{h}{P1} \right)^{-0.27} \left(\frac{P2}{P1} \right)^{-1.4} \quad \text{----- (22)}$$

With a correlation coefficient = 0.94.

A comparison between $E\%$ values predicted by equation (22) and observed values experimentally is shown in figure (12) .The maximum and minimum difference between them were 7.8 and -7.7 respectively.




Fig.(11) Variation of predicted values of Cd with observed ones for all weir models




Fig.(12) Variation of predicted values of E% with the observed ones for all weir models

CONCLUSIONS

Based on the results and analysis of this study. The following main conclusions were summarized as:

- 1- The U/S water flow heads can be measured correctly at a location when $X/P1 > 2$ U/S of the weir.
- 2- Stepping broad-crested weirs will improve the discharge coefficient and the values of Cd were higher than in traditional weirs by 4%.
- 3- The selection of the weir when $P2/P1 = 0.5$ is the best to get higher Cd. While the weir when $P2/P1 = 0.32$ is the best selection for higher E%. The intersection point in Fig.(9) where the weir of $P2/P1 = 0.4$ gave $Cd = 0.968$ and $E\% = 37$
- 4- A mathematical model to compute Cdth was modified depending upon momentum equation and gave 4% difference for traditional weir while for weir model of $P2/P1 = 0.5$ gave difference of less than 2% in comparison with experimental values.
- 5- A linear relation was obtained to estimate $(h/P1)$ in terms of $(H/P1)$ as shown in Eq.(20).
- 6- Two empirical power relations were obtained, the first to estimate Cd in terms of the ratio for U/S water head to U/S weir height $(H/P1)$ and the ratio of D/S weir height to U/S weir height $(P2/P1)$ as shown in Eq. (21). While the second relation to estimate E% in terms of the ratio for D/S water head to U/S weir height $(h/P1)$ and the ratio of D/S weir height to U/S weir height $(P2/P1)$ as shown in Eq.(22).

REFERENCES

1. Ackers, P., White, W.R., Perkins, J.A. and Harrison, A.J.M. (1978)," Weirs and Flumes for Flow Measurement", First Edition, John Wiley and Sons, Inc., New York, N.Y., PP. 133-166.
2. Al-Talib, A.N.J. (2007)," Laboratory Study of Flow Energy Dissipation Using Stepped Weirs", MSc. Thesis, Engineering College, Mosul University.
3. Chamani, M.R. and Beirami, M.K. (2002)," Flow Characteristics at Drops", Journal of Hydraulic Engineering, ASCE, Vol. 128, No. 8, PP.788-791.
4. Chanson, H. (2001)," Hydraulic Design of Stepped Spillways and Downstream Energy Dissipaters", Dam Energy, Vol.11, No.4, PP. 205-242.
5. Clemmons, A.J., Replogle, J.A. and Bos, M.G. (1984), "Rectangular Measuring Flumes for Lined and Earthen Channels", Journal of Irrigation and Drainage Engineering, ASCE, Vol.110, No.2, PP.121-137.
6. Gonzalez, C. A. and Chanson, H. (2007)," Experiment Measurements of Velocity and Pressure Distributions on a Large Broad-Crested Weir", Flow Measurement and Instrumentation, Vol.18, PP.107-113.
7. Noori, B. M. and Juma, I. A. (2009),"Performance Improvement of Broad Crested Weirs", Journal of Al-Rafidain Engineering, Mosul University, Vol.17,No.2,PP.95-107.
8. Ramamurthy, A.S., Tim, U.S. and Rio, M.V.J. (1988),"Characteristics of Square-Edged and Round- Nosed Broad-Crested Weirs ", Journal of Irrigation and Drainage Engg., ASCE, Vol.99, No.2, PP.61-73.
9. Rao, N. S. L., and Rao, M. V. J. (1973),"Characteristic of Hydrofoil Weirs", Journal of Hydraulic Engineering, ASCE, Vol.99, No.2, PP. 259-281.